



NOTES

1. Type of ramp to be bituminous material on primary and secondary roads and granite setts for tertiary roads.
2. Height of ramp shall be approved by SCC. Heights between 50 and 75mm according to situation.
3. All bullnose kerbs to be cut in half.
4. Position of humps shall comply with the Highways (Road Humps) Regulations 1999.
5. Minimum length of plateau of flat topped hump shall be 2500mm, pedestrian crossing points shall be 3000mm min. and on bus routes 6000mm min.
6. Block paving shall be 80mm laid in 45° herringbone pattern.
7. Blocks shall be colour grey, buff, red or brindle.
8. The sanded joints shall be sealed with a stabilizing compound.
9. For cross section detail refer the drawing no. DM-1100-22.



Growth, Highways & Infrastructure
 Suffolk County Council
 Endeavour House
 8 Russell Road
 Ipswich
 Suffolk IP1 2BX

DRAWING TITLE
 KERBS, FOOTWAYS, CYCLEWAYS AND PAVED AREAS
 SPEED TABLE RAISED
 ON TERTIARY ROADS

REV.	DESCRIPTION	CHECKED	DATE

INIT.	DATE	PROJECT TITLE	
RY	07/2024	STANDARD CONSTRUCTION DETAILS	
SH	07/2024	SCALE	DATE
RY	07/2024	N.T.S.	JUL. 2024
TK	07/2024	DRAWING No. DM-1100-43	